

Acclarix AX3 Series

Diagnostic Ultrasound

Version 2.0

Technical Specification

The remarkable Acclarix AX3 series Compact Ultrasound System delivers a powerhouse combination of features to meet the demands of point-of-care and general imaging applications. The Acclarix AX3 series has been designed from the ground up with a relentless focus on delivering unexpected levels of innovation and performance at a price point that is equally surprising. Dual active transducer ports design enables switching transducer seamlessly at a finger tip. Dual batteries extend the imaging scanning. Extremely light body embodied with brand new EIS operating system empowers smooth system operation and fast system response.



Advanced Technique and Features

TAI-Tissue Adaptive Imaging

eSRI- Adaptive Speckle Reduction Imaging

Frequency Compounding Imaging

Adaptive Spatial Compounding Imaging

Harmonic Imaging

Digital Multi-Beam forming

Trapezoid Imaging

Adaptive Doppler imaging

Spectrum Enhancement

Digital Zoom

Full Screen Zoom

Auto Doppler trace

Anatomic M mode

TDI mode-Tissue Doppler Imaging

3D/4D Imaging

Needle Visualization

eLearn Instruction software

ECG synchronization

Color M mode

Elastography mode

Panorama

B mode one-key Optimization

PW mode one-key Optimization

Color mode one-key Optimization

Auto IMT

Auto OB

Auto NT

Auto EF

Auto Vessel Diam*

Auto FHR

eLive

eVol.Flow

ECG Wave

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

System Overview

System Architecture

Physical Channels	64
Digital Channels	≤1105920
Gray Scale	256
Beam Forming	Eight beam
Processor	ARM
Memory	2 GB
Hard Drive	120GB/512GB/1TB SSD/2TB SSD
Operating System	Android
System Boot-up	About 30s
Boot-up from sleep	6s(Sleep mode) 10s(Deep Sleep mode)
Shutdown	3s

Dimensions and Weight

Main unit dimensions	395 mm × 385 mm × 64mm (without cushion)
Weight	≤4.5kg (without battery and any other accessory)

Monitor

- 15.6" high resolution **LED** monitor
- Resolution: 1920 x 1080
- Image Size: 1040*780
- Open angle:0° -180°
- Magnetic latch closure
- Built-in stereo speaker
- Brightness and Contrast adjustable
- Color temperature adjustable

Transducer Ports

- Dual active transducer ports
- Single or Dual transducer ports configurable
- One MTC module is supported, and maximum four transducers can be connected simultaneously.

Battery

- Rechargeable Li-ion Battery
- Max. two batteries configurable (two batteries with

6800mAh*2 capacity)

- For 6800mAh capacity battery
 - Approximately 1.5 hour of typical ultrasound exam use for one fully charged battery.
 - Approximately 3 hours of typical ultrasound exam use for two fully charged batteries.
 - One battery fully charged in about 3.5 hours
 - Two batteries fully charged in about 6.5 hours.
- Removable
- Battery indicator on the console near the handle.
- Battery level icon displayed on the main screen.
- Up to 18 hours Standby time (two fully charged batteries) in Deep Sleep mode.

AC Power Requirements

Voltage	100 -240 V~
Frequency	50 Hz/60 Hz

Environment Requirements

Operating Environment

Ambient temperature	0° to 40° C
Relative Humidity	15%~95% (no condensing)
Atmospheric pressure	86kPa-106kPa

Storage Environment

Ambient temperature	-20° to 55° C
Relative Humidity	15%~95% (no condensing)
Atmospheric pressure	70kPa-106kPa

Language Supported

- English
- Chinese
- German
- French
- Italian
- Spanish
- Russian
- Portuguese
- Polish

I/O Ports

- S-Video
- USB 3.0
- USB 2.0(two)

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

- HDMI
- Ethernet

Options

- Transducers
- Needle Guide Bracket Kits
- Printers
- Battery
- 512GB/1TB SSD/2TB SSD
- WIFI
- Footswitch
 - Single button/Double buttons
 - User-defined Functions(Freeze, Save, Print)
- Simple Cart: MT-808
 - Height Variable (0~200±10mm)
 - Length 602 ± 5mm, width 600 ± 5mm and height (849~1049)±5mm
 - A drawer for glossary storage
 - A shelf for Video printer
 - 4transducer holders and 2 gel holders with removable silicon cover
 - Cable manager
 - Drawer height and position adjustable
- Simple Cart MT-818
 - Height Variable (0~200±10mm)
 - Length 530 ± 5mm, width 570 ± 5mm and height 893 ± 10mm
 - A basket for glossary storage
 - A shelf for Video printer
 - 6 transducer holders with removable silicon cover
 - Cable manager
 - Basket height and position adjustable
- Suitcase
- MTC module
- ECG module
- External DVD drive
- Coupling gel

System Ergonomic Design

Dual Transducer Ports

Dual active transducer ports design enables switching transducer seamlessly at a finger tip, and reduces the workload of disconnecting/connecting transducers during an exam.

Handle

Provides wrist support during imaging.

Magnesium alloy body

Extremely light weight realizes the true portability.

User Interface

Control Panel

- Interactive back-lighting
- Hard Keys provides tactile feedback
- User-defined keys
- Physical trackball

Touch Screen

- 10.1” Touch screen
- Gesture-control
- Virtual TGC sliders
- Support visual Chinese, English QWERTY keyboard, German QWERTZ keyboard and French AZERTY keyboard for text input
- Brightness adjustable

Main Screen Display

Information Field

- EDAN logo
- Hospital name
- Date
- Time
- Patient ID
- Patient Name
- Patient Gender
- Patient Age
- Transducer model
- Exam Preset
- LMP/BBT, GA, EDD
- User Name

Image Field

- Mechanical Index (MI)
- Thermal Index (TI)

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



- Imaging parameters
- Gray Scale bar
- Depth Scale
- Center Mark
- Measured result window
- TGC curve

Measurements Menu Field

- Available generic and application measurements for current exam preset.
- Pre-categorized measurement groups.
- Consistent with the display on Measurement Touch Screen (10.1-inch).

Thumbnail Field

- All captured static images and cine clips
- Quick preview of thumbnails in image area
- Shortcut keys for selecting, viewing, deleting, exporting images.
- Display of catheter size reference.

User Feedback Field

- Illustration of trackball and trackball keys
- Cine bar
- Exit icon for exiting RawData review status.
- The active function of user-defined key F1 and F2.
- PIP display

Status Bar

- Utility Icon(access to Utilities function)
- Image Store Icon
- USB Icon
- Printer Icon
- WIFI Icon
- Network Transfer Status Icon
- Hard Drive Icon
- Battery Icon
- DVD icon

User Login Management

- Supports User Login at boot up and at exiting the sleep mode.
- Supports user type of Administrator and Operator
- Supports switching users without powering off the

system.

- Support Emergency login for emergency use.

Other Features

- eLearn instruction tool for basic scanning and nerve blocks.
 - Support instructions for OB&GYN, Nerve block, and GI (ABD, Cardiac, etc.) scanning.
 - Provides descriptions of Transducer position, Scan technique, Standard ultrasound image, Anatomy, Needle guide, tips, etc.
 - The illustration pictures can be enlarged to full touch screen display by pressing it.
- One-key full screen zoom(3 levels) by user-defined key F1 or F2.

Exam Presets

- System pre-defined exam presets include(Transducer specific) :
 - ABD
 - ABD Difficult
 - EM ABD
 - Aorta
 - FAST
 - Early OB
 - OB
 - EM OB
 - Fetal Echo
 - GYN
 - IVF
 - Urology
 - Prostate
 - Thyroid
 - Breast
 - Testis
 - Carotid
 - Up Ext A (Upper Extremity Artery)
 - Up Ext V (Upper Extremity Vein)
 - Low Ext A (Lower Extremity Artery)
 - Low Ext V (Lower Extremity Vein)

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

- Vascular
 - Vascular Access
 - EM VAS
 - Spine
 - MSK
 - Sup MSK (Superficial MSK)
 - EM MSK
 - Nerve
 - Sup Nerve (Superficial Nerve)
 - Shoulder
 - HIP
 - Adult Cardiac
 - Pediatric Cardiac
 - EM Adult Card
 - Pediatric Abdomen
 - Neonatal Abdomen
 - Neonatal Head
 - TCD
 - Needle-SMP
- User customizable presets: Copy, Delete, Save as and rename
 - Exam presets are configurable in Set-up.
 - Supports a second page, up to 30 presets per transducer.
 - Each preset can share comment, body mark, and measure presets.
 - The display order of the exam presets of each transducer can be adjusted per user's needs.

- User customizable
- English Comments Library is supported when the system language is not in English.

Body Mark

- Up to 143 Body Mark graphics in library
- Support separate body mark in Dual/Quad mode.

Annotations

Comments

- User-programmable home position
- Arrow with user controlled orientation
- Five language soft keyboard: Chinese, English, French, German, Russian.
- Block move and delete for separate blocks of text
- Smart text replacement for predefined text (e.g., Long replaces Trans with one keystroke)
- 545 pre-defined comments

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Imaging

Imaging Modes

B-mode

M-mode

- M-mode
- Linear Anatomic M mode
- Curved Anatomic M mode
- Color M mode

Color Doppler

- Velocity-based color Doppler
- PDI
- DPDI

PW Doppler

CW Doppler

TDI mode

- TVI
- TEI
- TVD
- TVM

3D/4D mode

Elastography Mode

Display Modes

Dual Imaging

- Available for B and Color(PDI/DPDI) mode.
- Displays two image side-by-side, two frozen or one active/one frozen.
- Allows to switch between two images.
- Measurements and calculations are supported on each image and across the dual images.
- Annotations are supported on both images.

Quad Imaging

- Available for B and Color (PDI/DPDI) mode.
- Displays images in four quadrants, four frozen or one active/three frozen.
- Allows to switch between four images.
- Measurements and calculations are supported on each image.
- Annotations are supported on each image.

Imaging Mode Combinations

- B+M
- B/C (PDI or DPDI), Single
- B/C(PDI or DPDI), Dual
- B/C(PDI or DPDI), Quad
- B+B/C(PDI or DPDI),Dual live
- B+Color (PDI or DPDI) +M
- B+PW (Duplex)
- B+PW (Update)
- HPRF
- B/C(PDI or DPDI)+PW (Triplex)
- B/C(PDI or DPDI)+PW (Update)
- B+CW (Update)
- B/C(PDI or DPDI)+CW (Update)
- B+TVI
- B+TVI+TEI
- B+TVI+TVD(Update)
- B+TVI+TVD(Triplex)
- B+TVM(Update)
- B+E

Imaging Parameters

B- mode(Live imaging)

Image Type	Detail/General/Penetration
Auto(one-key optimization)	TGC, Gain
Digital Zoom	x0.8-x2.0
Display Depth	1-45cm
Frequency	1-17MHz Max. 5 fundamental + 5 harmonic(depends on transducer)
Frequency display	Bandwidth, Frequency points
eSRI	Off, Low, Med, High
FOV	Small, Med, Large, Full
Steer	0° , ±10°
Gain	0-100dB, 1dB/step
TGC	8 segments
LGC	8 segments

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

Dynamic Range	40-96dB, 2dB/step
Line Density	Low, Med, High ≥512 lines
Frame Rate	Linear Transducer: Max. 532f/s, depends on transducer; Convex Transducer: Max. 48f/s at 18cm depth and Full FOV; Phased transducer: Max. 77f/s at 18cm depth and Full FOV.
Map	11 Types
Persistence	Off, Low, Med, High
Focus Position	Max. 16 positions, adjustable
Focus Number	1-3, adjustable
Colorize	On, off
Tint	5 Types
Up/Down Flip	
Left/Right Flip	
Spatial Compounding	On/ off ,max 3angles
Trapezoid	8,12,20, off (Linear transducer) Max. 10° left/right extended angle
Acoustic Power	10%-100%, 10%/step
Quick Rotation	0° ,90° ,180° ,270°
Panorama	On, Off Real-time speed indicator 360° rotation of Panoramic image

B- mode(Post-processing & retrospective)

- Gain
- TGC
- LGC
- Zoom
- Dynamic range
- eSRI
- Colorize
- Map

- Up/Down Flip
- Left/Right Flip
- Quick Rotation

M- mode(Live imaging)

Sweep Speed	Fast/High/Med/Low/ Slow Corresponds to sweep time of 1s, 2s, 4s, 8s and 12s per screen respectively.
Line Persist	Off, Low, Med, High
Map	11 Types
Colorize	On, off
Tint	5 Types
Gain	0-100dB, 1dB/step
Frequency	1-17MHz Max. 5 fundamental + 5 harmonic (depends on transducer)
Dynamic Range	40-96 dB, 2dB/Step
Strip size	Full, large, Med., small
Side-by-side	On(Left/Right) Off(Up/Down)
Acoustic Power	10%-100%, 10%/step
Linear Anatomic	On, off
M Mode	Up to 3 linear sample lines Adjustable angle of each sample line
Curved Anatomic	On, off
M Mode	Free-hand drawing of sample line; Sample line supports edition and deletion.

M-mode(Post-processing & retrospective)

- Gain
- TGC
- Dynamic range
- Colorize
- Map
- Stripe Size
- Side-by-side

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

Color/PDI/DPDI Mode(Live imaging)

Image Type	HighFlow/MidFlow/LowFlow
Dual Live	
ROI size/position	Adjustable
Frequency	Max. 5 levels (depends on transducer)
Gain	0-100dB, 1dB/step
Line Density	Low, Med, High
Dynamic Range	10-70 dB, 5dB/step Not available for Color mode
Frame Rate	Linear Transducer: Max. 350f/s, depends on transducer; Convex Transducer: Max. 8f/s at 18cm depth, Full FOV and biggest ROI; Phased transducer: Max. 14f/s at 18cm depth, Full FOV and biggest ROI.
Persistence	Off, Low, Med, High
Smooth	Off, Low, Med, High
Wall Filter	Low, Med, High
Color Map	8 Types
Steer Angle	0° , ±15° , ±30° (L12-5Q,Thyroid) 0° , ±10° , ±20° (L12-5Q,Low Ext V) 0° , ±10° , ±15° (L12-5Q,Up Ext A) 0° , ±5° , ±10° (L17-7SQ,MSK)
PRF	0.6- 11.4kHz
Max.PRF	0.1-21.7 kHz (L12-5HQ, Vasc Acc)
Baseline	25 levels (Not available for PDI mode)
Threshold	0-100
Invert	On, off (Not available for PDI mode)

Acoustic Power	10%-100%, 10%/step
Color Hide	On, off
Panorama	On, Off
	Real-time speed indicator
	360 ° rotation of Panoramic image
Auto(one-key optimization)	Gain

Color/PDI/DPDI Mode**(Post-Processing & Retrospective)**

- Zoom
- Color map
- Invert(Not available for PDI mode)
- Baseline
- Color Hide
- Vel Distr

PW mode(Live imaging)

Image Type	High Flow/Mid Flow/Low Flow
HPRF	Automatic invocation to maintain gate location/scale
Auto Trace	
Trace Side	Up, down, both
Duplex	Max. FR: 43f/s, depends on transducer
Triplex	Max. FR: 11f/s, depends on transducer
Frequency	2 levels
PRF	0.9- 14.7kHz
Max.PRF	0.34 - 27.9kHz (L12-5HQ, Vasc Acc)
Gain	0-100dB, 1dB/step
Dynamic Range	10-70 dB, 5dB/step
Wall Filter	Low, Med, High
Sweep Speed	Fast/High/Med/Low/ Slow Corresponds to sweep time of 2s, 3s, 4s, 6s and 8s per screen respectively.

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Baseline	9 levels
Angle Correction	-80° to 80°
Quick Angle	-60° /-45° /-30° /-15° /0° /15° /30° /45° /60 °
Steer	0° ,±15° , ±30° (L12-5Q,Thyroid) 0° ,±10° ,±20° (L12-5Q,Low Ext V) 0° ,±10° , ±15° (L12-5Q,Up Ext A) 0° ,±5° ,±10° (L17-7SQ,MSK)
Invert	
Volume	0-99
Map	11 Types
Colorize	On, off
Tint	5 Types
Gate Size	0.5-40 mm
Strip size	Full, large, Med., small
Auto (One-key Optimization)	Gain, DR or Scale/Baseline, user configurable
Acoustic Power	10%-100%, 10%/step
PW velocity	Max. 4.5m/s (correct angle 60°); Max. 13m/s (correct angle 80°) Min. 2mm/s (Non-noise signal)
Side-by-side	On(Left/Right) Off(Up/Down)

PW Mode (Post-Processing & Retrospective)

- Gain
- Dynamic Range
- Colorize
- Map
- Baseline
- Angle Correction
- Invert
- Strip size

- Auto trace
- Trace side
- Quick Angle
- Side-by-side

CW mode(Live imaging)

Image Type	HighFlow/MidFlow/LowFlow
PRF	1- 100kHz
Gain	0-100dB, 1dB/step
Dynamic Range	10-70 dB, 5dB/step
Wall Filter	Low, Med, High
Sweep Speed	Fast/High/Med/Low/ Slow Corresponds to sweep time of 2s, 3s, 4s, 6s and 8s per screen respectively.
Baseline	9 levels
Angle Correction	-80° to 80°
Quick Angle	-60 ° /-45 ° /-30 ° /-15 ° /0 ° /15 ° /30 ° /45 ° /60 °
Invert	
Volume	0-99
Map	11 Types
Colorize	On, off
Tint	5 Types
Strip size	Full, large, Med., small
Acoustic Power	10%-100%, 10%/step
CW velocity	Max. 72m/s Min. 1cm/s
Auto Trace	
Trace Side	Up, down, both
Side-by-side	On(Left/Right) Off(Up/Down)

CW Mode (Post-Processing & Retrospective)

- Gain
- Dynamic Range
- Colorize
- Map
- Baseline

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

- Angle Correction
- Invert
- Strip size
- Auto trace
- Trace side
- Quick Angle
- Side-by-side

TVI Mode(Live imaging)

Image Type	High Flow /Mid Flow /Low Flow
Dual Live	B+ TVI
ROI size/position	Adjustable
Frequency	2 levels
Gain	0-100dB, 1dB/step
Line density	Low, Med, High
Persistence	Off, Low, Med, High
Smooth	Off, Low, Med, High
Wall Filter	Low, Med, High
Color Map	8 types
PRF	0.6- 3.5kHz
Baseline	25 levels
Threshold	0-100
Invert	On, off
Acoustic Power	10%-100%,10%/step
Color Hide	On, off

TVI Mode (Post-Processing & Retrospective)

- Zoom
- Baseline
- Color map
- Invert
- Color Hide

TVD(PW-TDI) mode(Live imaging)

Image Type	HighFlow/MidFlow/LowFlow
Triplex	B+TVI+TVD
PRF	0.9- 5.9kHz
Frequency	2 levels

Gain	0-100dB, 1dB/step
Dynamic Range	10-70 dB, 5dB/step
Wall Filter	Low, Med, High
Sweep Speed	Fast/High/Med/Low/ Slow (Corresponds to sweep time of 2s, 3s, 4s, 6s and 8s per screen respectively.)
Baseline	9 levels
Angle Correction	-80° to 80°
Quick Angle	-60°/-45°/-30°/-15°/0°/15°/30°/45°/ 60 °
Invert	On, Off
Volume	0-99
Map	11 types
Colorize	On, off
Tint	5 Types
Gate Size	0.5-40 mm
Strip size	Full, Large, Med., Small
Acoustic Power	10%-100%, 10%/step
Auto Trace	
Trace Side	Up, down, both
Side-by-side	On(Left/Right) Off(Up/Down)

TVD (Post-Processing & Retrospective)

- Gain
- Dynamic Range
- Colorize
- Map
- Baseline
- Angle
- Quick Angle
- Invert
- Auto trace
- Trace side
- Gate Size
- Side-by-side

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



3D/4D mode (Live imaging)

Acquisition modes	3D, 4D
Visualization modes	Volume rendering, Multi-Slice modes
Multi-Slice	Max. 21 slices can be displayed on the same screen; Distance between each slice is 0.5-10.0mm
VOI size/Position	Adjustable
Render modes	Surface, Max.
3D clip	
Cut tools	Trace, Box, Eraser
Cut functions	Undo, Undo all, Redo
Display formats	Single 3D, Dual(A-plane + 3D), Quad(A/B/C Planes + 3D)
3D parameters	Threshold, Smooth, Brightness, Contrast, Tint
eFace	EDAN auto show face
4D frame rate	Max. 6vps
eLive	EDAN light rendering mode. On, Off

Elastography mode (Live imaging)

Opacity	1, 2, 3, 4 levels
Smooth	Off, Low, Med., High
Persistence	Off, Low, Med, High
Map	0-6
DR	0-6
Invert	On, Off

Elastography Mode

(Post-Processing & Retrospective)

- Opacity
- Map
- DR
- Invert

Review and Post-Processing functions

Cine Review

- Frame by frame manual review

- Auto playback with 6-level speed adjustable
- Start frame and end frame are selectable for cine loop review.
- Independent cine review in Dual/Quad mode.
- Maximum cine memory depends on transducers and image parameters:
 - 100000 frames for B mode
 - 30000 frames for Color mode
 - 180s for M mode
 - 240s for PW/CW Doppler mode

Post-Processing Features

All the image/cine is stored in Raw Data format in local disk. The following Post-Processing features are available when in image/cine review of current exam or the stored exam.

- Adjusting imaging parameters
- Measurements
- Annotations
- Storing static image/ cine loop

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Transducers and Biopsy Guide

Transducer Applications

Transducer		Applications	Transducer		Applications
C5-2Q		Abdomen Fetal / Obstetrics Urology Gynecology Musculoskeletal	E8-4Q		Fetal / Obstetrics Gynecology Trans-vaginal Trans-rectal Urology
L12-5Q		Small parts Peripheral Vascular Abdomen Musculoskeletal	P5-1Q		Adult Cardiac Abdomen Pediatric Cardiac Adult Cephalic
L17-7HQ		Small Parts Peripheral Vascular Musculoskeletal	L17-7SQ		Intra-operative Musculoskeletal Peripheral Vascular
C5-1Q		Abdomen Fetal / Obstetrics Urology Gynecology Musculoskeletal	C6-2MQ		Fetal / Obstetrics Abdomen Gynecology
MC8-4Q		Pediatric Abdomen Neonatal Cephalic Musculoskeletal Peripheral Vascular	MC9-3TQ		Pediatric Abdomen Neonatal Cephalic Musculoskeletal Peripheral Vascular
E10-3BQ		Fetal / Obstetrics Gynecology Trans-vaginal Trans-rectal Urology	E10-3HQ		Fetal / Obstetrics Gynecology Trans-vaginal Trans-rectal Urology
P7-3Q		Adult Cardiac Pediatric Abdomen	L12-5HQ		Small Parts (Breast, Testes, Thyroid) Peripheral Vascular

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

		Pediatric Cardiac Neonatal cephalic			Musculoskeletal Abdominal
ECL12-3Q *		Urology Gynecology	L12-5WQ *		Peripheral Vascular Musculoskeletal Small Parts
E10-3Q*		Fetal / Obstetrics Gynecology Trans-vaginal Trans-rectal Urology	C5-2XQ*		Abdomen Fetal/Obstetrics Urology Gynecology

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

Transducer Specifications

Transducer	C5-2Q	P5-1Q	L12-5Q	L17-7HQ	E8-4Q
Transducer Type	Convex	Phased	Linear	Linear	Intra-cavity
Bandwidth@ -6dB	2-5MHz	1-5MHz	5-11MHz	7-15MHz	4-8MHz
Center Frequency	3.8MHz	2.7MHz	8.0MHz	12.0MHz	6.2MHz
B Harmonic Frequencies(MHz)	H2~4/H3~5 / H2~5/ H3~4*	H2~4/H3~5	H6~10/H7~12	H9~13/ H10-17	H5~6/H5~8/H5~1 0/H6~11
B Fundamental Frequencies(MHz)	2~4/3~5/2~5	1~3/2~4/2~5	5~8/6~10/7~11	7~11/8~13/9~15	4~6/4~7/5~8
Spectrum Doppler Frequencies(MHz)	2.3/3.0	2.0/2.2	4.7/5.7	6.7/8.0	3.6/5.0
Color Doppler Frequencies(MHz)	2.2/2.7/3.2	2.0/2.5	5.2/5.9	6.7/8.0	3.6/4.7
Elements	128	64	128	192	128
Footprint	NA	16 mm	38mm	38mm	NA
Convex Radius	60mm	NA	NA	NA	10mm
FOV	60°	90°	NA	NA	150°
Display Depth	45cm	30cm	11cm	11cm	14cm
Biopsy Guide	Yes	Yes	Yes	Yes	Yes
Cable Length	2.0m	2.0m	2.0m	2.0m	2.0m

Transducer	C5-1Q	P7-3Q	L17-7SQ	MC8-4Q	MC9-3TQ
Transducer Type	Convex	Phased	Linear	Micro Convex	Micro Convex
Bandwidth@ -6dB	2-5MHz	3-7MHz	7-15MHz	4-9MHz	3-9MHz
Center Frequency	3.25MHz	4.9MHz	12.0MHz	6.5MHz	6.5MHz
B Harmonic Frequencies(MHz)	H2~4/H3~5/H2~5 / H3~6	H5~7/H6~8	H9~13/ H10-17	H4~7/H5~7/H5~8 / H5~10/H6~10	H5~8/H6~9
B Fundamental Frequencies(MHz)	2~4/3~5/2~5	3~5/4~6/ 5~7	7~11/8~13/ 9~15	4~5/4~6/4~7/ 5~8/6~9	3~6/4~7/5~9
Spectrum Doppler	2.3/3.0	2.7/3.8	6.7/8.0	4.2/5.0	3.6/4.5

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Frequencies(MHz)					
Color Doppler Frequencies(MHz)	2.9/3.2/3.5	2.5/3.0	6.7/8.0	4.2/5.0	3.6/4.5
Elements	160	96	128	128	128
Footprint	NA	15 mm	26mm	NA	NA
Convex Radius	50mm	NA	NA	15mm	10mm
FOV	64°	90°	NA	100°	150°
Display Depth	45cm	18cm	11cm	15cm	15cm
Biopsy Guide	Yes	No	No	Yes	Yes
Cable Length	2.0m	2.0m	2.0m	2.0m	2.0m

Transducer	C6-2MQ	E10-3BQ	E10-3HQ	L12-5HQ	C5-2XQ*
Transducer Type	Wobbler	Intra-cavity	Intra-cavity	Linear	Convex
Bandwidth@ -6dB	2-5MHz	4-8MHz	4-8MHz	5-11MHz	2-5MHz
Center Frequency	4.11MHz	6.5MHz	6.5MHz	8.0MHz	3.4MHz
B Harmonic Frequencies(MHz)	H2~4/H3~5/ H2~5	H5~6/H5~8/ H5~10/H6~11/ H6~13	H5~6/H5~8/H5~ 10/H6~11/ H6~13*	H6~10/H7~12/H 8~10/ H8~11/ H8~12	H2~4/H3~5/H2~5/ H3~4
B Fundamental Frequencies(MHz)	2~4/3~5/2~5	4~6/4~7/5~8	4~6/4~7/5~8	5~8/6~10/7~11/ 8~10	2~4/3~5/2~5
Spectrum Doppler Frequencies(MHz)	2.6/3.0	3.6/4.8	3.6/4.8	4.7/5.2	2.3/3.0
Color Doppler Frequencies(MHz)	2.6/3.0/3.3	4.0/4.5/5.0	4.0/4.5/5.0	5.2/5.9/7.2/7.5/7 .9	2.2/2.7/3.2
Elements	128	192	192	192	128
Footprint	NA	NA	NA	38mm	NA
Convex Radius	40mm	10mm	10mm	NA	60mm
FOV	64°	190°	190°	NA	60°
Display Depth	30cm	14cm	14cm	11cm	45cm

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Biopsy Guide	No	Yes	Yes	Yes	No
Cable Length	2.0m	2.0m	2.0m	2.0m	2.0m

Transducer	L12-5WQ*	E10-3Q*	ECL12-3Q*	
Transducer Type	Linear	Intra-cavity	Convex (R10)	Linear
Bandwidth@ -6dB	5-11 MHz	4-8MHz	4-8 MHz	5-11 MHz
Center Frequency	8.0MHz	6.5MHz	6.5MHz	8.0MHz
B Harmonic Frequencies(MHz)	H6~10/H7~12/H8~10/ H8~11/ H8~12	H5~6/H5~8/H5~10/ H6~11/H6~13	H5~6/H5~8/ H5~10/H6~11/ H6~13	H6~10/ H7~12
B Fundamental Frequencies(MHz)	5~8/6~10/7~11/8~10 0	4~6/4~7/5~8	4~6/4~7/5~8	5~8/6~10/7~11
Spectrum Doppler Frequencies(MHz)	4.7/5.2	3.6/4.8	3.6/4.8	4.7/5.7
Color Doppler Frequencies(MHz)	5.2/5.9/7.2/7.5/7.9	4.0/4.5/5.0	4.0/4.5	4.7/5.2
Elements	256	128	192	192
Footprint	51mm	NA	NA	58mm
Convex Radius	NA	10mm	10mm	NA
FOV	NA	150°	200°	NA
Display Depth	11cm	14cm	14cm	11cm
Biopsy Guide	Yes	Yes	Yes	
Cable Length	2.0m	2.0m	2.0m	

NOTE: The asterisk "*" indicates that the frequency type is related to the transducer version. Among them: optimized C5-2Q probe (02.01.212622015) add harmonic frequency type H3~4 and optimized E10-3HQ probe (02.01.214791011) add harmonic frequency type H6~13.

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Biopsy Guide

- **Needle Guide**

- Supports guide lines of multiple angles.
- Supports single and parallel guide line.
- Supports depth and length mark on guide line.
- Support guide line calibration.

- **Need Visualization**

- Supports three needle inserted angles for linear transducers

- **Center Line**

- Center Line is a vertical dotted line displayed at the middle of the image field, representing the middle of ultrasound beam. It helps to locate the position and depth of a target disease focus for out-of-plane biopsy, lithotripsy and etc.

- **Supported Needle Guided Brackets**

Model	Type	Angle/Depth	Description
BGK-CR10UA	In-plane	2°	For use with the E8-4Q/E10-3Q*, Supports: 16G-18G
BGK-002	In-plane	38° , 46° , 58°	For use with the L12-5Q/L17-7HQ/L12-5HQ, Supports: 14G-23G
BGK-003	Out-of--plane	0.5cm, 1.0cm, 1.5 cm, 2.5 cm, 3.5 cm	For use with the L12-5Q/L17-7HQ/L12-5HQ, Supports: 21G-22G
BGK-004	In-plane	12° , 20°	For use with the MC9-3TQ, Supports: 14G-23G
BGK-005	In-plane	0°	For use with the E10-3BQ, Supports: 16G-18G
BGK-006	In-plane	1°	For use with the E10-3HQ, Supports: 16G-18G
BGK-008	In-plane	12° , 22°	For use with the P5-1Q, Supports: 14G-23G
BGK-009	In-plane	14° , 20° , 32°	For use with the C5-1Q Supports: 14G-23G
BGK-007	In-plane	18° , 25° , 35°	For use with the C5-2Q, Supports: 14G-23G
BGK-010	In-plane	44° , 53° , 64°	For use with the L12-5WQ* Supports: 14G-23G

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

BGK-012	In-plane	11° , 20° , 37°	For use with the MC8-4Q, Supports: 14G-23G
BGK-013	In-plane	0.5cm, 1.0cm, 1.5cm, 2.0cm, 2.5cm, 3.0cm, 3.5cm, 4.0cm, 4.5cm, 5.0cm	For use with the ECL12-3Q* Supports: 18G

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Measurements

- Default measurement unit options
 - Distance: mm, or cm
 - Area: mm², or cm²
 - Volume: mm³, or cm³
 - Velocity: cm/s, m/s
- Caliper Size: switch automatically according to the distance (3 sizes)
- Dynamic display of measurement results
- Reposition caliper
- Pre-categorized measurement groups based on clinical applications; Configurable in Measure Preset. Measured results of each measurement are configurable in Measure Preset.
- Measurements displayed on main screen and touch screen are consistent.

General Measurements

B-mode

- Distance (Dist. 2 Point, Ratio D1/D2, Length Trace, Stenosis% Dist.)
- Circumference/Area (Area Ellipse, Area Trace, Area Spline, Ratio A1/A2, Stenosis% Trace, Stenosis% Ellipse, Stenosis% Spline)
- Angle(Angle 3-point, Angle 2-line)
- Volume(Volume 3 Dist., Ellipse 1 Dist.)
- Stenosis
 - %Dist Stenosis(Distance)
 - % Area Stenosis (Ellipse, Trace, Spline)
- Vessel
 - Vessel Diameter (2-point, Ellipse)
 - Volume flow area
 - IMT

M-mode

- Distance(2-point method)
- Ratio D1/D2(2-point method)

- Time
- Slope
- HR
- Tei index: COT, ET

Doppler mode

- PS
- ED
- RI
- PI
- PS,ED,RI,S/D
- Time
- HR
- Manual Trace
- Spline Trace
- Auto Trace(Max. 15 measured results are configurable)
- Velocity
- PGMax
- PGMean
- Volume Flow
- Tei index: COT, ET
- dp/dt

Elastography mode

- Eratio(Ellipse, Trace)

Application Measurements/calculations

Abdomen

B-mode:

- Liver
 - Length, Width, Height
 - Volume(calculation)
 - Portal Vein Diameter
 - Common Hepatic Duct
- Gallbladder
 - Length, Height
 - Gallbladder Wall Thickness

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

- Common Bile Duct
- Pancreas
 - Head, Body, Tail, Duct
- Spleen
 - Length, Height
- Renal
 - Length, Width, Height
 - Volume(calculation)
 - Renal Cortex Thickness
- Aorta Diameter
- Bladder
 - Pre-void bladder (Length, Width, Height)
 - Post-void bladder Length, Width, Height)
 - Micturated Volume
 - Pre-void bladder volume
 - Post-void bladder volume

PW mode:

- Abdominal Aorta
- Superior Mesenteric Artery
- Inferior Mesenteric Artery
- Hepatic Artery
- Splenic Artery
- Renal Artery
- Portal Vein
- Inferior Vena Cava
- Main Portal Vein
- Hepatic Vein
- Middle Hepatic Vein
- Splenic Vein
- Superior Mesenteric Vein
- Inferior Mesenteric Vein

M mode:

- IVC-CI

Gynecology

B-mode:

- Uterus

- Length, Width, Height
- Endometrium Thickness
- Uterus body
- Uterus volume
- UT Cavity
- UT-L/CX-L(calculation)
- Cervix
 - Length, Width, Height
 - UT-L/CX-L(calculation)
- Ovary
 - Length, Width, Height
 - Ovary volume
- Follicle
- Cyst
- Fluid POD
- Pelvic Floor
 - BSD(R)
 - BSD(S)

PW mode:

- Uterine Artery
- Ovary Artery

Obstetrics

B-mode:

● Fetal Biometry	BPD, HC, AC, FL, HUM, CER, OFD, NF, TAD, APAD, THD, APTD, TTD, FTA
● Early Gest	CRL, BPD, FL, HUM, NT, GS, YS, AF
● Long Bones	HUM, ULNA, RAD, TIB, FIB, Foot
● Fetal Cranium	CER, NT, NF, LVW, CM, NB,PNT, BOD
● AFI	Q1, Q2,Q3,Q4
● Ovary	Ovary L, Ovary W, Ovary H

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

• Chamber	LV Diam, LA Diam, RV Diam, RA Diam
• LVOT/AO	LVOT Diam, Ao Asc, Ao Arch, Ao Isthmus, Desc Ao
• RVOT/PA	RVOT Diam, MPA Diam, Ductus A
• CTAR	Area 1, Area 2

PW mode:

- MCA
- Umb. A
- Placenta A
- Ovary A
- Ut. A
- Fetal Ao
- Desc Aorta
- SMA
- IVC
- Ductus V
- FHR
- MV
- TV
- MPV
- Ductus A

M-mode:

- FHR

Cardiac

B-mode:

• LV Simpson	A4C Dias., A4C Sys., A2C Dias., A2C Sys.
• LV Study	LVSTd, LVIDd, LVPWd, IVSTs, LVIDs, LVPWs
• LV/RV	LVIDd, LVIDs, RVAWd, RVIDd
• LA/Ao	LA, AoD
• Aorta	Ao Asc, AoD

• RVOT Diam	RVOT Diam
• LVOT Diam	LVOT Diam
• PV	PV Diam
• RVDs	RVDs
• LA/RA	RA length, RA Width, LA length, LA width
• LVM(A-L) (Left Ventricular Mass)	LVAd Sax Epi, LVAd Sax Endo, LVAd Apical
• LVM (T-E) (Left Ventricular Mass)	LVAd Sax Epi, LVAd Sax Endo, a, d
• LVM (Cube)(Left Ventricular Mass)	LVSTd, LVIDd, LVPWd
• MVA	
• AVA	

M-mode:

• LV Study	LVSTd, LVIDd, LVPWd, IVSTs, LVIDs, LVPWs
• LV/RV	LVIDd, LVIDs, RVAWd, RVIDd
• Time	LVET, LV PEP, RV PEP
• Mitral Valve	MV D-E Exc, MV D-E Slope, E-F Slope, EPSS, MV E-E Sep, MV A-C Interval, MAPSE
• TAPSE	TAPSE
• LA/Ao	LA, AoR Diam, RVOT Diam, ACS
• HR	HR
• LVM (Cube)(Left Ventricular Mass)	LVSTd, LVIDd, LVPWd

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

• IVC-CI	IVCmax, IVCmin, , IVC-CI(cal)
PW mode:	
• Mitral Valve	E/A, MV PHT, MV VTI, IVRT, MV A Duration, MV DecT, MR Vmax, MR VTI, MV E Duration, MV HR
• Tricuspid Valve	TV VTI, TV Vmax, TV E/A, TV HR, TR Vmax
• AV	LVOT VTI, LVOT Vmax, AV VTI, AV HR, AV Vmax, AV Accel Time, AV Decel Time, AR VTI, AR Vmax, AR Accel Time, AR PHT, AR Decel Time
• PV	PV VTI, PV Vmax, PR Vmax, PV Accel Time, PV HR
• PV Vein	PVein S Vel, PVein D Vel, PV A Vel, PV A Dur
• Hep Veins	Hep S Vel, Hep D Vel, Hep A Vel, Hep A Dur
• RVSP	TR Vmax ,RA Pressure
• AVA(VTI)	LVOT VTI, AV VTI
• CO(LVOT)	LVOT VTI, AV HR
• TDI	S Medial, E' Medial, A' Medial, S Lateral, E' Lateral, A' Lateral
• PISA	MR Trace, AR Trace, TR Trace, PR Trace
• Qp/Qs	LVOT VTI, RVOT VTI
C- mode:	
• PISA	MR Rad, MR Als. Vel, AR Rad, AR Als. Vel, TR Rad, TR Als. Vel, PR Rad, PR Als. Vel

Urology

B-mode:

- Renal
 - Length, Width, Height
 - Renal Cortex Thickness
- Bladder
 - Pre-void Bladder (Length, Width, Height, volume)
 - Post-void Bladder (Length, Width, Height, volume)
 - Micturated Volume
- Prostate
 - Length, Width, Height
- Seminal
 - Length, Width, Height
- Testis
 - Length, Width, Height

PW mode:

- Renal Artery
- Arcuate Artery
- Segmental Artery
- Interlobar Artery

Small Parts

B-mode:

- Thyroid
 - Length, Width, Height
 - Thyroid Isthmus
- Breast
 - Lesion1, Lesion2, Lesion3, Lesion4, Lesion5
- Testis
 - Length, Width, Height

PW mode:

- Superior Thyroid Artery
- Inferior Thyroid Artery

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.

Vascular		
<ul style="list-style-type: none"> Carotid 	<p>B-mode:</p> <p>Common Carotid Artery Intima-Media Thickness, Internal Carotid Artery Intima-Media Thickness, Carotid Artery Bifurcation Intima-Media Thickness</p> <p>PW mode:</p> <p>Common Carotid Artery, External Carotid Artery, Internal Carotid Artery, Vert Artery, Subclavian Artery, HR, Volume Flow</p>	<p>PW mode:</p> <p>Common Femoral Vein, Deep Femoral Vein, Superficial Femoral Vein, Common Iliac Vein, External Iliac Vein, Internal Iliac Vein, Great Saphenous Vein, Popliteal Vein, Peroneal Vein, Posterior Tibial Vein, Anterior Tibial Vein, Small Saphenous Vein, Volume Flow</p>
	<ul style="list-style-type: none"> Upper Extremity Artery 	<p>PW mode:</p> <p>Subclavian Artery, Axillary Artery, Brachial Artery, Ulnar Artery, Radial Artery, HR, Volume Flow</p>
<ul style="list-style-type: none"> Upper Extremity Vein 	<p>PW mode:</p> <p>Subclavian Vein, Axillary Vein, Brachial Vein, Cephalic Vein, Basilic Vein, Ulnar Vein, Radial Vein, Median Cubital Vein, Volume Flow</p>	<p>B mode:</p> <p>Volume Flow</p> <p>B mode:</p> <p>Volume Flow Area</p>
<ul style="list-style-type: none"> Lower Extremity Artery 	<p>PW mode:</p> <p>Common Femoral Artery, Deep Femoral Artery, Superficial Femoral Artery, Common Iliac Artery, External Iliac Artery, Internal Iliac Artery, Popliteal Artery, Peroneal Artery, Posterior Tibial Artery, Anterior Tibial Artery, Dorsalis Pedis Artery, HR, Volume Flow</p>	<p>PW mode:</p> <p>Anterior Cerebral Artery, Middle Cerebral Artery, Posterior Cerebral Artery, Anterior Communicating Artery, Posterior Communicating Artery, Basilar Artery, Vertebral Artery, Internal Carotid Artery</p>
		<p>B mode:</p> <p>Vessel Diam</p> <p>B mode: Vessel Diam</p>
<p>Pediatrics</p> <p>B-mode:</p> <ul style="list-style-type: none"> Left lateral ventricle Right lateral ventricle left trigone right trigone Hip joint(with dislocation type) <ul style="list-style-type: none"> HIP Angle HIP d/D 		

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.



Emergency

- EM Abdpacage
- EM OB package
- EM Card package

Reports

- Editable worksheet
- The appearance of worksheet can be toggled between dark and light modes.
- Report type: ABD, GYN, OB, URO, VAS, SMP, FETAL, CARD, PED, Nerve, MSK
- Comments/Findings section
- Support fetal growth curve and grow bar display; supports data display of max. 4 fetus
- Support Fetus Score*;support add Fetus Score to the report
- Support data of multiple fetus
- User-imported Report Header
- User-defined hospital logo
- Multiple number of selected images
- Multiple layouts of image in report.
- Support select all images to add into the report
- Report Layout supports auto adjust.
- Support zoom in preview
- Support Export as PDF format
- Support print by report printer.
- Support custom report information
- Support display BMI and BSA
- Some information supports to adjust its display order in the report
(Measurements/Growth Curve/Image/Fetus Score Result/Findings/Comment)
- Support display the time of system's first use displayed in the report

- Static image/Cine clip is stored in local disk in RawData format.
- Two dedicated hard keys on the console for capturing static image and cine clips respectively.
- Cine clips supports prospective and retrospective storing.
- The length of cine clip is configurable.
- Prospective storing: max. 2 min length of clip can be stored in real-time scanning.
- Retrospective storing: all the clip data in the cine buffer can be stored in cine review mode, max.2 min.
- Supports up to 30,000(for 120GB hard disk)or 150,000(for 512GB hard disk) or350,000(for ITB hard disk) lossless single frames
- Supports cine clips exported:
 - Up to 100000 frames for B mode
 - Up to 30000 frames for Color mode
 - Up to 180s for M
 - Up to 240s for PW/CW mode

Exam Database

- Support exam storage without patient information
- Support exam query
- Support review current exam or prior exam
- Support review images of an exam
- Support review report of an exam
- Support export images as BMP,JPEG, TIFF, Raw Data or DICOM format
- Support export cine clip as AVI, MP4, WMV, Raw Data or DICOM format
- Support export Report as PDF format
- Support export exams (including patient information, images)
- Support compare images

Image Storage & Exam Archiving

Image Storage

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Examlist

- Support for historical exam search and automated information entry.

Exam Archiving

All Clips and Static images stored on the system are stored internally in Raw Data format. They can be archived to other storage device for long-term storage as described below.

- Archived to DICOM server.
- Archived to FTP server.
- Archived to USB device.

Note: If a clip length exceeds 3s, when selecting to export in DICOM format to a DICOM server or USB stick, only the last 3s of the clip will be exported for this release.

- Burned to DVD disk
- Sent to mobile devices.

Connectivity

Network

- Wired network connection
- Wi-Fi connection

DICOM 3.0 Service

- DICOM Storage
 - Connectivity to DICOM server for storage of all static images or cine clips with patient information.
 - Manual-Transfer in background on Demand.
 - Auto-Transfer when store or at exam end.
 - Transfer management UI for viewing transfer task status, retransferring a task or deleting a transfer task.
 - Transfer process encrypted.
 - Supports Structured Report transferring: OB, GYN, Cardiac and Vascular.
- DICOM Modality Worklist
 - Enables query of the patient worklist

schedule from hospital information system to the ultrasound system via DICOM network connection.

- Query of worklist on demand or on start of exam.
 - Populates the Patient Information screen with patient demographic information automatically when one patient is selected.
 - Displays/hides the ended exams in the worklist
 - Query conditions can be configured to quickly filter exam information.
 - MPPS
 - The MPPS service automatically sends the exam status to the MPPS server at the start and the end of the ultrasound exam.
 - Displays Additional Materials item on patient information page.
 - Storage Commitment
 - Supports using the port information of the storage commitment server to receive storage commitment information
 - Supports the establishment of a new association for receiving storage commitment information
 - DICOM Query/Retrieve
 - Supports entering key words for query prior exams from DICOM server.
 - Supports download a queried exam to local disk for reviewing.
 - DICOM Print
 - Prints the images remotely via a DICOM printer which connects to a DICOM server.
 - Multiple parameters for printing are configurable.
- ### FTP Network Store Service
- Supports to transfer exams to FTP servers for

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

storage in the background.

- Transfer management UI for viewing transfer task status, retransferring a task or deleting a transfer task.
- A PDF report can be sent to FTP server together with the exam.

CloudShare

- Supports sending image/clips to mobile devices by scanning the QR code on main screen when CloudShare icon is clicked.

Time Synchronization

- Sets the system time to synchronize with the network time

Supported Peripherals

Printers

The system supports the connection of Video printers and report printers. The report can be connected locally via USB connector or remotely via network connection. Printer drivers can be imported to the system for the support of more report printers.

- Video printers
 - SONY UP-X898MD
 - SONY UP-D25MD
 - SONY UP-25MD
- Local report printers
 - HP Officejet Pro 251dw
 - HP LaserJet Pro 200 color M251n
 - HP LaserJet CP1525n Color
 - HP Deskjet Ink Advantage 2010
 - HP Deskjet 1010
 - HP Deskjet 1510
 - HP LaserJet 400 M401d
 - HP DeskJet Ink Advantage Ultra 2029
 - HP DeskJet 1112
 - Canon E518

- Canon iP2780
- HP LaserJet Pro MFP M126nw
- EPSON L310
- HP DeskJet 1050
- HP DeskJet 2050
- HP LaserJet M252n
- EPSON L130
- HP Color LaserJet Pro M254nw
- HP Color Laser 150a
- HP Color Laser 150nw
- [HP Laser 1008a](#)
- EPSONL3118
- Photo printer
 - [Cannon CP1500](#)
 - [Medion Healthcare GRAPIX](#)
- Network report printer

Mini PC

Safety and Regulatory

The Acclarix AX3 series Diagnostic Ultrasound System have been designed, manufactured and tested to comply with the following internationally recognized standards:

- IIEC 60601-1: Medical Equipment Safety
- IEC 60601-1: Medical Equipment Safety
- IEC 60601-1-2: Medical Device Electromagnetic Safety
- IEC 60601-2-37: Ultrasonic Medical Equipment Safety
- IEC 62133: Battery Safety
- IEC 62304: Medical Device Software Life-cycle Process
- IEC 62366: Medical Device Usability Engineering
- EN ISO 14971: Medical Device Risk Management
- ISO 10993-1 Biological evaluation of medical devices — Part 1: Evaluation and testing within a risk management process sheet

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Revision History

Version	Revisions	Date
1.0	Updated for R1.02 release.	2019-5-24
1.1	Updated for R1.1 release. See the changes highlighted with blue color.	2019-9-12
1.2	Updated for R1.2 release. See the changes highlighted with blue color.	2020-02-09
1.3	Updated for R1.21 release: Updated the DICOM store function.	2020-03-26
1.4	Updated for R1.40 release. See the changes highlighted with blue color.	2020-09-17
1.5	Updated for R1.41 release. See the changes highlighted with blue color.	2020-11-25
1.6	Updated for R1.50 release. See the changes highlighted with blue color.	2021-02-20
1.7	Updated for R2.00 release. See the changes highlighted with blue color.	2021-11-15
1.8	Updated for R2.10 release. See the changes highlighted with blue color.	2022-04-10
1.9	Updated for R2.20 release. See the changes highlighted with blue color.	2022-08-29
2.0	Updated for R2.40 release. See the changed highlighted with blue color.	2024-01-08

This datasheet applies to Acclarix AX3 series Diagnostic Ultrasound Systems, including Acclarix AX3, Acclarix AX3 Exp, Acclarix AX3 Super, Acclarix AX25, Acclarix AX28, Acclarix AX2, Acclarix AX2 Exp, Acclarix AX2 Super, Acclarix AX15 and Acclarix AX18 models. The configuration difference between each model is listed in the following table.

Models	Configuration Difference			
	Feature 1	Feature 2	Feature 3	Feature 4
	Seminal Vesicle Meas.	Testis Meas.	Fluid POD	3D/4D
Acclarix AX3	√	√	√	√
Acclarix AX3 Exp	√	X	√	√
Acclarix AX3 Super	X	X	√	√
Acclarix AX25	X	√	√	√
Acclarix AX28	√	X	X	√
Acclarix AX2	√	√	√	X
Acclarix AX2 Exp	√	X	√	X
Acclarix AX2 Super	X	X	√	X
Acclarix AX15	X	√	√	X
Acclarix AX18	√	X	X	X

*Feature is subject to regulatory approval, and may not be available for sale in specific countries.

Features and specifications are subject to change without prior notice. No reproduction, copy or transmission may be made without written permission. Not all products or features are available in all countries, contact Edan for local availability.